AT WORK

## L39-B3

- Engine model: Weichai WP6G125E22
- Rated power: 92 kW/2200 rpm
- Operating weight: 10.8 t

## **Product features**

L39-B3 is an all-new designed 3t long-wheelbase planetary transmission loader product. It's mainly applicable for medium/ small-scale aggregate yards, mixing stations, small coal mines, farmlands, pastures, and urban and road constructions. With longer wheelbase, it can features more extensive application scenes.







							Standard Arm	Extended Arm	Long Arm
L39-E	01	verall length	7148mm	7275 mm	7395 mm				
Technical specifications:					0	verall width	2518mm	2518 mm	2518 mm
	lincation	15.			01	verall height	3235mm	3235 mm	3235 mm
		Operating weight			10800 kg				
	GENERAL SPECIFICATIONS	Rated Load			3000 kg				
		Bucket capacity			1.8 m <sup>3</sup>				
		Breakout force			105 kN				
		Static tipping load (full turn)			6000 kg				
		Dumping height (Standard/Extended/Long)			2875/3057/3200 mm				
		Dumping reach (Standard/Extended/Long)			955/906/886 mm				
		Engine model			Weichai WP6G125E22				
	ENGINE	Туре			In-line, water-cooled, 6-cylinder, direct injection, turbocharged				
		Rated power			92 kW				
	ENG	Rated speed			2200 rpm				
		Displacement Maximum torque			6.75 L 510 N·m				
		Maximum torque							
_		Minimum fuel co	nsum	ption	193.8 g/kW·h		_	_	
	TRAVEL SPEED	Gear	-	1st	2nd		3rd	4th	_
		Forward		0~12.5 km/h	0~38 km/h		_	_	
		Reverse		0~16.4 km/h	-		_	_	
<b>در</b> . ۹	ES AND FINAL DRIVES	DRIVE SYSTEM			Four-wheel drive				
		Gradeability			30°				
		Maximum traction			110 kN				
			Service brakes		Air over hydralic disc brakes on 4 wheels				
		BRAKE SYSTEM:	Park	ing brake	Manual parking brake				
	NALD	STEERING SYSTEM:	Туре	2	Articulated type, full-hydraulic power steering				
	ND FI		Max	imum steering angle	38° each direction				
			Turnir	ng Radius to Outside of Tires	5415 mm				
	AX		Turnir	ng Radius to Outside of Bucket	6036 mm				
		TIDEC	Туре	2	17.5-25 12PR				
			Patt	ern level	L3				
				Center distance of tires 1856 mm					
		TIRES	Cent	ter distance of tires	183011111				
		TIRES		ter distance of tires eel base	2900 mm				
		TIRES						_	_

OVERALL DIMENSIONS

► THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.







## CEBU # 88 Block 4, North Reclamation Area, DAVAO # 88 Block 4, North Reclamation A Subangdaku, Mandaue City, Cebu Philippines, 6014 Tel.: + 6332 346-2297; 346-0171; 343-8608; 422-3789 Fax: +6332 346-2295 Mobile: +63 977-811-9796

8 Dacudao Ave., Davao City Email: davao.sales@3in1group.ph Tel.: 082 322-6514 Mobile: +63 917-148-4628

MANILA 107 Roosevelt Ave., SFDM Brgy. Paraiso, Quezon City Tel.: +632 426-6000 Email: cyr.gella@3in1group.ph Mobile: +63 917-712-5765

Standard Arm Extended Arm Long Arm